

TREATED PINE CLEAR



Exterior Clear Timber Finishes for Treated Softwoods

PRODUCT DATA SHEET

Description

TREATED PINE CLEAR – A clear oil based exterior timber finish specially formulated for use on treated pine. It has been formulated using environmentally acceptable ingredients.

TREATED PINE CLEAR takes away the normally dry treated pine look and its penetrating qualities give the timber a rich natural oiled look, which enhances the natural grain and beauty of pine. It keeps the treated timber surface clean by eliminating blackening and discolouration.

TREATED PINE CLEAR contains water repellents which help stabilize the timber and reduce checking and movement thus overcoming many of the problems associated with using pine in service.

TREATED PINE CLEAR is formulated to dry slowly in service to avoid a film forming on the timber surface, so peeling or cracking is never a problem.

Recommended Uses

TREATED PINE CLEAR can be used wherever a clear protective exterior finish is required e.g. cladding, decking, pergolas, trellis and fencing, etc. TREATED PINE CLEAR is suitable for all treated softwood such as Radiata Pine and Slash Pine. Use Preschem AUSSIE CLEAR on all other popular outdoor timbers, e.g. Cedar, Jarrah, Cypress Pine, Oregon, etc.

Restrictions

Water based paints should not be applied directly over fresh applications of TREATED PINE CLEAR as they may not give satisfactory adhesion. If wood treated with TREATED PINE CLEAR is to be painted or stained, allow either a long period of weathering before application or use an oil based formulation. Do not apply TREATED PINE CLEAR when dew or rain is expected.

Surface Preparation

Apply TREATED PINE CLEAR over dry surfaces, free from dirt, grease and wax. Previously varnished or painted surfaces must be thoroughly stripped. Badly weathered surfaces should be sanded back or cleaned using a suitable wood cleaner containing oxalic acid or similar chemical before application.

Directions for Use

TREATED PINE CLEAR can be applied by any convenient means, such as brush, roller, spray or dip application. Apply one generous coat of TREATED PINE CLEAR. A minimum of 3 days drying time for decking and area subject to foot traffic is advisable. Ensure all end grain wood is well coated with TREATED PINE CLEAR to minimize water absorption.

Maintenance

Timber treated with TREATED PINE CLEAR will not blacken when maintained regularly. However, over time and depending on the severity of exposure, the colour of the treated timber will fade. Repeat applications are simple as the timber can be re-oiled to bring back the timber texture. Areas that wear due to heavy foot traffic e.g. decks, doorways, steps, etc can be touched up when necessary. Each application contributes to an accumulation of TREATED PINE CLEAR building up deep within the treated timber providing a barrier against biodegradation. After the first 12 months of weathering, a 2nd application of TREATED PINE CLEAR will ensure a much longer service life. Alternatively apply AUSSIE CLEAR to give the timber a rich golden teak look.

Coverage

Depending on surface porosity, one litre of TREATED PINE CLEAR will normally cover up to 10 square metres on dressed timber or 6 square metres on sawn timber.

Clean Up

Clean applicators thoroughly with mineral turpentine.

Packaging

TREATED PINE CLEAR is available in 1,4 and 20 litre cans.

Technical data

Flash Point	66°C (Abel Closed Cup)
Colour	Light Amber Liquid
Sheen	Flat
Density	0.930 at 20°C
Viscosity	19.5 mm ² /s (cSt) at 20°C

Safety Instructions

Avoid skin contact by wearing protective clothing. Don't breathe vapour of spray mist.

First Aid Instructions

If poisoning occurs, contact a doctor or Poison Information Centre.

Eyes: Hold eyes open, flood with water for at least 15 minutes – see a doctor.

Skin: Remove contaminated clothing and wash skin thoroughly with soapy water.

Inhalation: Remove to fresh air.

If Swallowed: **DO NOT** induce vomiting. Give a glass of water to drink and transport to hospital.

Manufactured By:

PRESCHEM PTY LTD

(A.C.N. 006 867 929)

Cheltenham Victoria 3192

Telephone: 03 9532 0679 Facsimile: 03 9532 1041 Web Site Address: www.preschem.com.