



AUSSIE CLEAR SPRAY

SAFETY DATA SHEET

Date	May 2019
Issue	008

SDS 02

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND SUPPLIER

Product Name: PRESICHEM AUSSIE CLEAR SPRAY

Product Code: ACSPAY

Recommended use: Oil-based exterior finish for use on timber to prevent blackening.

Supplier: PRESICHEM Pty Ltd
ABN 41 314 509 336
147 – 149 Herald Street
Cheltenham Victoria 3192
Australia

Telephone: +61 3 9532 0679 or 1800 641 711

Facsimile: +61 3 9532 1041

Emergency Phone: +61 3 9574 2792 or +61 3 9574 8128 (Business hours)

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.

Hazard Pictograms



DG Class: 2.1
Subsidiary Risk: None allocated
UN Number: 1950 (Aerosols)
HAZCHEM Code: None allocated
Poison Schedule: Not Scheduled

Hazard Statement(s):

H302: Harmful if swallowed.
H316: Causes mild skin irritation.
H223: Flammable aerosol.

Precautionary Statement(s):

P102: Keep out of reach of children
P260: Do not breathe vapour
P301+P310+P331: IF SWALLOWED: Call a Doctor or Poison Information Centre on 13 11 26. Do not induce vomiting.



AUSSIE CLEAR SPRAY

SAFETY DATA SHEET

Date	May 2019
Issue	008

SDS 02

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical identity	CAS Number	Proportion
Distillates (petroleum), hydrotreated light	64742-47-8	20 – 30 %
Hydrocarbon Propellant	106-97-8	20-30%
Alkyd resin	Proprietary	10 – 30 %
3 - (Iodo-2Propynyl butyl carbamate)	55406-53-6	<0.5%
Ingredients determined not to be hazardous	Proprietary	to 100 %

All components in this product are listed on the Australian Inventory of Chemical Substances (AICS).

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre on 13 11 26.

Swallowed: If conscious, dilute stomach contents by giving large amounts of water. Seek medical attention or transport person to hospital. Do not attempt to induce vomiting or give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Eye: Flush eyes with plenty of water for a minimum of 15 minutes. Keep rotating the eyes to ensure complete flushing. Seek medical attention promptly if irritation persists or any loss of vision occurs.

Skin: Immediately remove contaminated clothing. Wash skin thoroughly with soap and water. Launder contaminated clothing before re-use. Seek medical advice if skin irritation occurs or persists.

Inhaled: Remove promptly to fresh air. If respiratory irritation, dizziness, nausea or unconsciousness occurs, seek immediate medical attention. Apply artificial respiration if breathing stops.

Notes to doctor: Symptomatic treatment. May cause central nervous system depression. Dermatitis may result from prolonged or repeated exposure. Potential for chemical pneumonitis. Consider gastric lavage with protected airway, administration of activated charcoal.

5. FIRE FIGHTING MEASURES

Specific hazards: Classified as a 2.1 Flammable Gas. Aerosol cans may explode with extreme heat. Sources of ignition should be kept clear. The vapour is heavier than air, and can spread along the ground and distant ignition is possible. The product will float and can be re-ignited on water.

Extinguishing media: Foam, water spray or fog. Dry chemical powder, carbon dioxide (CO₂), sand or earth may be used for small fires only.

Fire fighting procedures: Use water to cool fire-exposed containers and any adjacent containers. Firefighters must wear self-contained breathing apparatus with full protective clothing. During a fire, irritating or highly toxic gases may be generated by thermal decomposition or combustion.

Hazardous Decomposition Products: Predominantly carbon monoxide, carbon dioxide and organic compounds.

Hazchem Code: None allocated



AUSSIE CLEAR SPRAY

SAFETY DATA SHEET

Date	May 2019
Issue	008

SDS 02

6. ACCIDENTAL RELEASE MEASURES

Unprotected personnel should be kept away. Spill area is likely to become slippery underfoot – use care to avoid falling or slipping. Wear protective equipment (refer Section 8) to prevent skin and eye contamination and inhalation of vapours. Stop and contain large spills for salvage or absorb in inert absorbent material (e.g. sand, earth). Scoop spilled material into marked sealable containers for disposal or recovery by an approved method. Prevent run-off into drains and waterways. Wash the spill area with copious volumes of detergent to remove any trace amounts of product. The product will not mix with water. Ventilate area well and ensure adequate personal protection as above. Small spills can be absorbed with inert absorbent material and disposed in accordance with regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Keep containers tightly closed. Avoid ingestion and inhalation. Use only in a well-ventilated area. Wash clothing before reuse.

Storage: Store in tightly closed containers in cool, dry, isolated and well ventilated areas away from heat. Keep containers closed at all times – check regularly for leaks. Remove all ignition sources. Extinguish any naked flames. Do not eat, drink or smoke in areas of use or storage. Store with all precautions required for handling combustible liquids (AS 1940).

Incompatibilities: The product is incompatible with oxidising agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National occupational exposure standards

Substance	TWA	STEL	Carcinogen Category	Notices
Aliphatic solvents*	1200 mg/m ³	--	None allocated	None allocated
Butane Propellant	1900 mg/m ³	--	None allocated	None allocated

*Recommended by the supplier

As published on the Hazardous Chemical Information System (HCIS).

Exposure Standard (TWA) is the time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life. According to current knowledge this concentration should neither impair the health or, not cause undue discomfort to, nearly all workers.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These Exposure Standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering controls: Facilities storing or using this material should be equipped with eyewash and deluge safety shower. Use adequate ventilation to keep airborne concentrations low. Keep containers closed when not in use.

Personal Protection

Skin: Avoid skin contact by the use of approved chemical resistant gloves and aprons – PVC or Neoprene (AS 2161).

Eye: Avoid eye contact by wearing safety glasses with side-shields or non-fogging goggles (AS/NZS 1336). Eyewash and deluge safety shower should be provided in all areas where product is handled.

Respiratory: PII organic vapor respirator or mask as per AS 1715 and/or AS 1716



AUSSIE CLEAR SPRAY

SAFETY DATA SHEET

Date	May 2019
Issue	008

SDS 02

Protective clothing (gloves, coveralls, boots, etc.) should be worn to prevent skin contact. Direct skin contact should be avoided by wearing long sleeved shirts and long trousers. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	opaque amber aerosol with slight odour
Vapour pressure:	not available
Specific gravity:	0.84 (20°C - Concentrate)
Flash Point:	-60°C (Butane)
pH:	not available
Flammability Limits:	0.6 – 5.5 % (Vol.) (distillates (petroleum), hydrotreated light)
Solubility in water:	insoluble
Vapour Density:	not available
Viscosity:	18 mm ² /s (cST) (20°C, Concentrate)

10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal conditions of use.
Hazardous polymerization:	Will not occur.
Incompatible materials:	Strong oxidising agents.
Conditions to avoid:	Avoid heat, sparks, open flames and other ignition sources.
Hazardous decomposition products:	Predominantly carbon monoxide, carbon dioxide and organic compounds.

11. TOXICOLOGICAL INFORMATION

Swallowed: Unlikely under normal occupational exposures. Swallowing this product is likely to cause irritation to the gastrointestinal tract. Symptoms may include abdominal pain, nausea, vomiting, diarrhoea. Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Eye: The liquid may cause temporary irritation. Stinging, watering and redness of the eyes may result.

Skin: May cause slight to moderate skin irritation. Prolonged or repeated skin contact may cause defatting of the skin which could lead to dermatitis.

Inhaled: Prolonged inhalation of the vapour or mist may cause drowsiness, dizziness, nausea and headache. Central nervous system depression may occur with slowing of reflexes, fatigue and incoordination.

Chronic: Repeated or prolonged skin contact may dryness and defatting, resulting in dermatitis.

Acute toxicity: No toxicity data is available for this material. The following toxicity data is applicable for the distillates (petroleum), hydrotreated light component present in this product:

Oral LD50 – rat: > 2000 mg/kg

Dermal LD50 – rat: > 2000 mg/kg

Inhalation LC50 – rat: > 4 g/m³/4 h



AUSSIE CLEAR SPRAY

SAFETY DATA SHEET

Date	May 2019
Issue	008

SDS 02

12. ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data is available for this material. The following ecotoxicity data is applicable:

Distillates (petroleum), hydrotreated light component present in this product: Toxicity to fish: LC50 > 1000 mg/L
3-iodo-2-propynyl butylcarbamate - LC50 = 0.067 mg/L

Persistence and degradability: Most components in this product are expected to be biodegradable.

Mobility in soil: Most components in this product are expected to adsorb to soil and have low mobility.

13. DISPOSAL CONSIDERATIONS

Suitable for disposal to approved landfill facility in accordance with local waste authority requirements. Recover or reuse if possible. Product is insoluble in water and should not be flushed to effluent treatment plants for treatment. Empty containers should be drained completely. Residues may cause an explosion hazard if heated above the flash point. Do not puncture, cut or weld uncleaned containers. Send to approved drum or metal recycler.

14. TRANSPORT INFORMATION

Road and Rail Transport (Australian Dangerous Goods Code):

UN Number: 1950 (Aerosol)
Proper Shipping Name: None allocated
Class: 2.1
Hazchem Code: None allocated
Packing Group: None allocated

Marine Transport (International Maritime Dangerous Goods Code):

UN Number: 1950 (Aerosol)
Proper Shipping Name: None allocated
Class: 2.1
Packing Group: None allocated
Marine Pollutant: No

Air Transport (International Air Transport Association Dangerous Goods Regulations):

UN Number: 1950 (Aerosol)
Proper Shipping Name: None allocated
Class: 2.1
Packing Group: None allocated

15. REGULATORY INFORMATION

Classification: Classified as a Hazardous Substance according to criteria of Safe Work Australia.
Classified as a Dangerous Good according to criteria of the Australian Dangerous Goods Code.

Poisons Schedule: Not Scheduled



AUSSIE CLEAR SPRAY

SAFETY DATA SHEET

Date	May 2019
Issue	008

SDS 02

16. OTHER INFORMATION

Australian Standards References:

- AS/NZS 1336 Recommended Practices for Occupational Eye Protection.
- AS/NZS 1715 Selection, Use and Maintenance of Respiratory Protective Devices.
- AS/NZS 1716 Respiratory Protective Devices.
- AS 1940 The Storage and Handling of Flammable and Combustible Liquids.
- AS 2161 Industrial Safety Gloves and Mittens (excluding electrical and medical gloves).

Preschem Pty Ltd SDS Contact Point:

OH&S / Quality Manager (Rohan Baker)
Telephone: 03 9532 0679
Facsimile: 03 9532 1041

This Safety Data Sheet has been prepared Preschem Pty Ltd.

Issue Date: 24/05/2019/RB

Supersedes Issue Date: Feb 2016

Reasons for Issue: Revision.

This Safety Data sheet is valid for 5 years from the date of issue and may be withdrawn and revised any time prior to that date. Please ensure that you are using the latest issue.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Preschem Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.